

Phenol Oil

Product Datasheet

Phenols and cresols are obtained from coal tar, usually as a mixture of the three stereoisomers – molecules with the same number and type of atoms but unique atom arrangements. All three isomers are very toxic, and in high concentrations can be absorbed in fatal amounts through the skin.

APPLICATIONS

- ◆ Used in low concentrations in sheep-dips – disinfectants often containing insecticides and pesticides
- ◆ Used in low concentrations as effective disinfectants and antiseptics
- ◆ Used as components of creosote, a wood preservative produced as a by-product of coal tar
- ◆ distillation
- ◆ Can be used in phenol-formaldehyde resins

PERFORMANCE

- ◆ It increases the lifespan of woods
- ◆ It increase the disinfectant property of several commercial and household chemicals

TYPICAL QUALITY PROPERTIES

Property	Unit	Specification
Specific Gravity @ 15.56°C	-	0.95 Min
p cresol	%	34 - 38
o cresol	%	15 - 18
BTX	%	06 - 09
Pyridine	%	02 - 04
Napthalene	%	02 - 04
Moisture	%	0.5

PACKAGING

Packing Type	Quantity
ISO Container, Drum, or Vessel	Drum or Tanker size

PRODUCT FORM AND SAFETY DATA

- ◆ Very toxic and in high concentrations can be absorbed in fatal amounts through the skin
- ◆ Dust or vapours of this product can cause irritation in the respiratory tract. This product can affect the central nervous system causing nausea, dizziness and loss of coordination.



Know more about
our coal tar
derivatives products

TECHNICAL AND SALES CONTACT

HEAD OFFICE

Upadrashta House, 48, Dr. V. B. Gandhi Marg, Fort, Mumbai – 400023 INDIA Contact number: +91-22-22712800



enquiry@epsiloncarbon.com